

DH3628DAW2Z

Cordless SDS-plus Rotary Hammer Drill

36V

4966376405572

NEW
BRUSHLESS
RFC
UVP
LVH
LED LEVEL

NEW

High performance: 3.2 J to drill up to 28 mm in concrete

User protection features

Compatible with Cyclon Dust Extraction Unit



Batteries not included

Specifications

Voltage		36V
Capacity	Concrete	28 mm
	Steel	13 mm
	Wood	32 mm
Impact energy		3.2 J
Full-load impact rate	Low	0 - 3,170 bpm
	Normal	0 - 4,300 bpm
No-load rotation speed	Low	0 - 700 rpm
	Normal	0 - 950 rpm
Full-load vibration level		12.1 m/s
Brushless motor		Yes
User Vibration Protection		Yes
Low Vibration Handle		Yes
Anti-kickback (RFC)		Yes
Auto-stop		Yes
LED level		Yes
Dimensions with BSL36A18 (L x W x H)		358 x 91 x 233 mm
Weight		3.2 kg

Characteristics

- High performance of 3.2 J to drill holes up to 28 mm in concrete
- Three modes: rotary hammer, drill only or hammer only with selectable chisel position for optimum versatility
- Reactive Force Control (RFC) stops the motor when the drill bit is suddenly blocked to reduce twisting of the tool to prevent potential injury
- User Vibration Protection (UVP): minimizes vibration levels in all circumstances to increase operator comfort
- Low Vibration Handle (LVH) for optimal work comfort and grip
- Compatible with Cyclon Dust Extraction Unit with HEPA filter to keep your working environment as safe and clean as possible
- LED level indicates if tool is held straight to achieve precisely drilled holes
- Auto-stop: record and store drilling time for consistent depth of holes
- Soft-start control for comfortable drilling without slipping
- Ergonomic soft grip handle for optimum control and operator comfort

Scope of delivery

DH3628DAW2Z: Stackable case HSC II



Cyclon Dust Extraction Unit
379135 In cardboard box.
379136 In stackable case HSC II.
 Max. drilling diameter 20 mm
 Operating stroke 100 mm
 Weight 1.0 kg

¹ Standard accessories vary by country or area.

Read everything about our services at hikoki-powertools.com

