

NT1850DFJXZ Cordless Brad Nailer

4966376335442



Lightweight and compact body

Steady nailing performance

Air Spring Drive System





Specifications	
Voltage	18V
Driving system	Air Spring
Magazine angle	0°
Applicable nail shank diameter	1 - 1.25 mm / 18 Gauge
Applicable nail length	16 - 50 mm
Nail loading capacity	100 nails
Cycle rate	2 nails /sec.
Motor type	Brushless motor
Selectable firing modes	Single sequential / contact
Toolless nailing depth control	Yes
Number of driven nails ¹	Up to 1,300
Sound power level LWA	79 dB
Emission sound pressure level	68 dB
Uncertainty KpA	3 dB
Weight bare tool	2.0 kg
Weight with BSL1820M ²	2.4 kg

Characteristics

Lightweight and compact body for optimum ease of operation Easily choose between sequential or bump fire mode for highest accuracy and fastest work progress

Steady nailing performance even at cold temperatures and high altitudes No need for compressors, hoses or gas canister increase user safety and ensure low maintenance costs

Brushless motor for high power, less wear and a long service life LED light for illuminating dark work spaces

Air Spring Drive System with compressed air for zero ramp-up time, low recoil and cosistently high power for fast work progress and easy maintenance

Versions³

NT1850DFJXZ: 2x battery BSL1820M, charger UC18YFSL, nose cap, stackable case HSC IV

NT1850DFJ6Z: Stackable case HSC IV NT1850DFJ4Z: Cardboard box

¹ Per charge with BSL1820M.

² Weight according to EPTA-2004 procedure.

³ Standard accessories vary by country or area.

Read everything about our services at **hikoki-powertools.com**

