



DH3640DA

SDS-max Cordless Rotary Hammer Drill

36V - 9.2 J - 40 mm





Highest performance in class: 9.2 J

Lightest weight in class

UVP & LVH for comfort and lowest vibration

Specifications		
Voltage		36V
Brushless motor		\checkmark
Impact energy		9.2 J
Capacity drill bit diameter		40 mm
Capacity core bit diameter		105 mm
No-load speed		250 - 500 /min.
Full load impact rate		1,400 - 2,800 /min.
Speed modes		4
Vibration level		10.3 m/s ²
UVP - counter weight		\checkmark
Low Vibration Handle		\checkmark
Trigger lock		\checkmark
LED light		\checkmark
Dimensions (L x W x H)		499 x 262 x 107 mm
Tool weight		6.1 kg
Weight with BSL36B18X ¹		7.4 kg

Characteristics

9.2 J of impact energy to perform drilling and demolishing applications fastest in class

Lightest tool in its class to keep user fatigue at a minimal level

UVP (User Vibration Protection): low vibration level for the highest degree of operator comfort

Low vibration handle (LVH) for optimal work comfort and grip

Reactive Force Control (RFC) stops the motor when the tool bit is suddenly overburdened to reduce twisting of the main unit and prevent potential injury

Trigger lock for chiseling allows for easy operation and continuous use

Constant speed control delivers extra power allowing the motor to maintain speed under load

Variable drilling speed control allows users to change speed to suit application

Versions²

DH3640DAW2Z:

Side handle, injection case

4966376407989

¹ Weight according to EPTA-2004 procedure.

² Standard accessories vary by country or area.

Read everything about our services at **hikoki-powertools.eu**

