



Specifications		
Voltage		36V
Capacity	Concrete	28 mm
	Steel	13 mm
	Wood	32 mm
Impact energy		3.2 J
Full-load impact rate	Low	0 - 3,170 bpm
	Normal	0 - 4,300 bpm
No-load rotation speed	Low	0 - 700 rpm
	Normal	0 - 950 rpm
Full-load vibration level		12.1 m/s
Brushless motor		Yes
Quick change chuck		Yes
User Vibration Protection		Yes
Low Vibration Handle		Yes
Anti-kickback (RFC)		Yes
Auto-stop		Yes
LED level		Yes
Dimensions with BSL36A18 (L x W x H)		389 x 91 x 232 mm
Weight		3.4 kg



Cyclon Dust Extraction Unit 379139 In cardboard box.

379140 In stackable case HSC II. Max. drilling diameter 20 mm Operating stroke 100 mm Weight 1.0 kg

¹ Standard accessories vary by country or area.

Characteristics

High performance of 3.2 J to drill holes up to 28 mm in concrete Three modes: rotary hammer, drill only or hammer only with selectable chisel position for optimum versatility

Quick change between the SDS-plus drill bit holder and the drill chuck holder for efficient use of the rotary hammer for various applications Reactive Force Control (RFC) stops the motor when the drill bit is suddenly blocked to reduce twisting of the tool to prevent potential injury User Vibration Protection (UVP): minimizes vibration levels in all circumstances to increase operator comfort

Low Vibration Handle (LVH) for optimal work comfort and grip

Compatible with Cyclon Dust Extraction Unit with HEPA filter to keep your working environment as safe and clean as possible

LED level indicates if tool is held straight to achieve precisely drilled holes Auto-stop: record and store drilling time for consistent depth of holes Soft-start control for comfortable drilling without slipping

Scope of delivery

DH3628DCW2Z: Stackable case HSC II

Read everything about our services at **hikoki-powertools.com**



Non-contractual presentation photos, the machines are delivered without accessories unless otherwise stated. HiKOKI reserves the right to change certain technical characteristics, as well as the accessories supplied as standard. All products presented fall within the limit of the available stocks of HiKOKI Power Tools.

HiKOKI 3 YEAR WARRANTY More information about our conditions at **hikoki-powertools.com**