

## WR36DF

Cordless Impact Wrench 36V - 3/4" - 2,400 Nm

4966376407644



BRUSHLESS
IP 56

## Powerful tightening torque

4 modes with Auto-stop/Auto-slow function

**IP56** for superior ingress protection

Specifications		
Voltage		36V
Capacity	Bolts	M12 to M36
	High tension bolts	M10 to M27
Tightening torque		1,900 Nm <sup>1</sup>
Nut busting torque		2,400 Nm
Square drive		3/4"
No-load speed	Mode 4	0 - 1,500 /min.
	Mode 3	0 - 1,200 /min.
	Mode 2	0 - 900 /min.
	Mode 1	0 - 600 /min.
Impact rate	Mode 4	0 - 2,600 /min.
	Mode 3	0 - 2,200 /min.
	Mode 2	0 - 1,900 /min.
	Mode 1	0 - 1,600 /min.
Motor type		Brushless
IP-rating		IP56
Auto-stop function		Yes
Auto-slow function		Yes
LED light		Yes
Dimensions (L x H)		221 x 290 mm
Weight with BSL36A18 <sup>2</sup>		3.9 kg

## Characteristics

Powerful tightening torque up to 1,900 Nm and nut busting torque up to 2,400 Nm for tough applications

4 modes with optional Auto-stop/Auto-slow function for best adjustability to various applications

Auto-stop function stops the tool after a preset time to prevent overtightening of bolts

Auto-slow function reduces speed automatically after loosening is detected to prevent bolts from dropping

IP56 for superior ingress protection for harshest weather conditions and dust resistance  $\,$ 

Integrated battery dampening system extends the life of the battery interface and the tool itself

Ergonomic soft grip for optimal ease of use safe and convenient handling Integrated LED light for a clear view of the work surface

## Version

WR36DFW2Z: Stackable case HSC III

Read everything about our services at **hikoki-powertools.co.uk** 



<sup>&</sup>lt;sup>1</sup> Tightening an M30 (10.9) bolt for 6 seconds.

<sup>&</sup>lt;sup>2</sup> Weight according to EPTA-2004 procedure.

<sup>&</sup>lt;sup>3</sup> Standard accessories vary by country or area.