

## WR36DG

Cordless Impact Wrench 36V - 1/2" - 2,000 Nm

496637407774





## **Powerful tightening torque**

4 modes with Auto-stop/Auto-slow function

**IP56** for superior ingress protection

Voltage         36V           Capacity         Bolts         M12 to M33           High tension bolts         M10 to M27           Tightening torque         1,400 Nm¹           Nut busting torque         2,000 Nm           Square drive         1/2"           No-load speed         Mode 4         0 - 1,500 /min.           Mode 3         0 - 1,200 /min.           Mode 1         0 - 600 /min.           Mode 1         0 - 600 /min.           Mode 3         0 - 2,200 /min.           Mode 3         0 - 2,200 /min.           Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Mode 2         0 - 1,600 /min.           Mode 3         0 - 2,200 /min.           Mode 1         0 - 1,600 /min.           Mode 1         0 - 2,200 /min.           Mode 2         0 - 1,600 /min.           Mode 3         0 - 2,200 /min. <td< th=""><th>Specifications</th><th></th><th></th></td<>	Specifications		
High tension bolts   M10 to M27	Voltage		36V
Tightening torque         1,400 Nm¹           Nut busting torque         2,000 Nm           Square drive         1/2"           No-load speed         Mode 4         0 - 1,500 /min.           Mode 3         0 - 1,200 /min.           Mode 2         0 - 900 /min.           Mode 1         0 - 600 /min.           Mode 3         0 - 2,500 /min.           Mode 3         0 - 2,200 /min.           Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Motor type         Brushless           IP-rating         IP56           Auto-stop function         Yes           Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm	Capacity	Bolts	M12 to M33
Nut busting torque         2,000 Nm           Square drive         1/2"           No-load speed         Mode 4         0 - 1,500 /min.           Mode 3         0 - 1,200 /min.           Mode 2         0 - 900 /min.           Mode 1         0 - 600 /min.           Impact rate         Mode 4         0 - 2,500 /min.           Mode 3         0 - 2,200 /min.           Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Motor type         Brushless           IP-rating         IP56           Auto-stop function         Yes           Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm		High tension bolts	M10 to M27
Square drive         1/2"           No-load speed         Mode 4         0 - 1,500 /min.           Mode 3         0 - 1,200 /min.           Mode 2         0 - 900 /min.           Mode 1         0 - 600 /min.           Impact rate         Mode 4         0 - 2,500 /min.           Mode 3         0 - 2,200 /min.           Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Motor type         Brushless           IP-rating         IP56           Auto-stop function         Yes           Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm	Tightening torque		1,400 Nm <sup>1</sup>
Mole of the properties of	Nut busting torque		2,000 Nm
Mode 3       0 - 1,200 /min.         Mode 2       0 - 900 /min.         Mode 1       0 - 600 /min.         Impact rate       Mode 4       0 - 2,500 /min.         Mode 3       0 - 2,200 /min.         Mode 2       0 - 1,900 /min.         Mode 1       0 - 1,600 /min.         Motor type       Brushless         IP-rating       IP56         Auto-stop function       Yes         Auto-slow function       Yes         LED light       Yes         Dimensions (L x H)       221 x 290 mm	Square drive		1/2"
Mode 2	No-load speed	Mode 4	0 - 1,500 /min.
Mode 1		Mode 3	0 - 1,200 /min.
Impact rate         Mode 4         0 - 2,500 /min.           Mode 3         0 - 2,200 /min.           Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Motor type         Brushless           IP-rating         IP56           Auto-stop function         Yes           Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm		Mode 2	0 - 900 /min.
Mode 3         0 - 2,200 /min.           Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Motor type         Brushless           IP-rating         IP56           Auto-stop function         Yes           Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm		Mode 1	0 - 600 /min.
Mode 2         0 - 1,900 /min.           Mode 1         0 - 1,600 /min.           Motor type         Brushless           IP-rating         IP56           Auto-stop function         Yes           Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm	Impact rate	Mode 4	0 - 2,500 /min.
Mode 1 0 - 1,600 /min.  Motor type Brushless  IP-rating IP56  Auto-stop function Yes  Auto-slow function Yes  LED light Yes  Dimensions (L x H) 221 x 290 mm		Mode 3	0 - 2,200 /min.
Motor type Brushless IP-rating IP56 Auto-stop function Yes Auto-slow function Yes LED light Yes Dimensions (L x H) 221 x 290 mm		Mode 2	0 - 1,900 /min.
IP-rating		Mode 1	0 - 1,600 /min.
Auto-stop function Yes Auto-slow function Yes LED light Yes Dimensions (L x H) 221 x 290 mm	Motor type		Brushless
Auto-slow function         Yes           LED light         Yes           Dimensions (L x H)         221 x 290 mm	IP-rating		IP56
LED light Yes Dimensions (L x H) 221 x 290 mm	Auto-stop function		Yes
Dimensions (L x H) 221 x 290 mm	Auto-slow function		Yes
	LED light		Yes
Weight with BSL36A18 <sup>2</sup> 3.9 kg	Dimensions (L x H)		221 x 290 mm
	Weight with BSL36A18 <sup>2</sup>		3.9 kg

## Characteristics

Powerful tightening torque up to 1,400 Nm and nut busting torque up to 2,000 Nm for tough applications

4 modes with optional Auto-stop/Auto-slow function for best adjustability to various applications

Auto-stop function stops the tool after a preset time to prevent overtightening of bolts

Auto-slow function reduces speed automatically after loosening is detected to prevent bolts from dropping

IP56 for superior ingress protection for harshest weather conditions and dust resistance

Integrated battery dampening system extends the life of the battery interface and the tool itself

Ergonomic soft grip for optimal ease of use safe and convenient handling Integrated LED light for a clear view of the work surface

## **Versions**<sup>3</sup>

WR36DGW2Z: Stackable case HSC III

<sup>1</sup> Tightening an M30 (10.9) bolt for 6 seconds.

Read everything about our services at **hikoki-powertools.co.uk** 



<sup>&</sup>lt;sup>2</sup> Weight according to EPTA-2004 procedure.

<sup>&</sup>lt;sup>3</sup> Standard accessories vary by country or area.