

## WH36DCJRZ

### Cordless Impact Driver

36V - 215 Nm - 114 mm

4966376401239

**NEW**

**215 Nm tightening torque**

**Unique Triple Hammer technology**

**Compact and lightweight:  
only 114 mm and 1.6 kg**



#### Specifications

Capacity	Small screws	4 to 10 mm
	Ordinary bolts	5 to 18 mm
	High tension bolts	4 to 14 mm
	Self drilling screw	Ø 3.5 to 6 mm
Tightening torque	Power mode	215 Nm
	Bolt mode	215 Nm
	Bolt single mode	95 Nm
	Self drilling screw mode	80 Nm
	Soft mode	76 Nm
Bit shank size	1/4" (6.35 mm)	
Type of motor	Brushless	
No load speed	Soft mode	0 - 900 /min.
	Bolt mode	0 - 2,900 /min.
	Bolt single mode	0 - 2,900 /min.
	Power mode	0 - 3,400 /min.
	Self drilling screw mode	0 - 3,700 /min.
Impact rate	Soft mode	0 - 2,000 /min.
	Self drilling screw mode	0 - 2,200 /min.
	Bolt mode	0 - 4,100 /min.
	Bolt single mode	0 - 4,100 /min.
	Power mode	0 - 4,100 /min.
LED light	Yes	
Dimensions (L x H)	114 x 241 mm	
Weight with BSL36A18 <sup>1</sup>	1.6 kg	
Center height	29 mm	

<sup>1</sup> Weight according to EPTA-2004 procedure.

<sup>2</sup> Standard accessories vary by country or area.

#### Characteristics

- Compact and lightweight for high operator comfort
- Powerful and fast: 215 Nm of tightening torque for the hardest jobs
- Brushless motor for long lifetime and high efficiency
- Sensitive trigger starts the tool at 100 rpm to prevent overtightening
- Three bright LEDs for best illumination and no shadows
- IP56 rating due to coated electronics for protection against splash water and dust
- 5 modes for best adjustability and efficient work
- Triple Hammer technology for greater operator comfort and less cam-out
- Bolt single mode stops tool automatically after 3-5 impacts to prevent overtightening of bolts

#### Standard accessories<sup>2</sup>

- 2x battery BSL36A18
- Charger UC18YSL3
- Stackable case HSC II

Read everything  
about our services at  
[hikoki-powertools.co.uk](http://hikoki-powertools.co.uk)

