

## WH18DCW2Z

### Cordless Impact Driver

18V - 210 Nm

4966376402946

**NEW**

**210 Nm torque for the hardest jobs**

**Sensitive trigger starts fastening operation at 100 rpm**

**Unique Triple Hammer technology**



Compatible with



#### Specifications

|                                   |                          |                 |
|-----------------------------------|--------------------------|-----------------|
| Capacity                          | Small screws             | 4 to 10 mm      |
|                                   | Ordinary bolts           | 5 to 18 mm      |
|                                   | High tension bolts       | 5 to 14 mm      |
|                                   | Self drilling screw      | Ø 3.5 to 6 mm   |
| Tightening torque                 | Power mode               | 210 Nm          |
|                                   | Bolt mode                | 210 Nm          |
|                                   | Auto stop mode           | 85 Nm           |
|                                   | Self drilling screw mode | 75 Nm           |
|                                   | Soft mode                | 69 Nm           |
| Bit shank size                    | 1/4" (6.35 mm)           |                 |
| Type of motor                     | Brushless                |                 |
| No load speed                     | Power mode               | 0 - 3,400 /min. |
|                                   | Bolt mode                | 0 - 2,900 /min. |
|                                   | Auto stop mode           | 0 - 2,900 /min. |
|                                   | Self drilling screw mode | 0 - 3,700 /min. |
|                                   | Soft mode                | 0 - 900 /min.   |
| Impact rate                       | Power mode               | 0 - 4,000 /min. |
|                                   | Bolt mode                | 0 - 4,000 /min. |
|                                   | Auto stop mode           | 0 - 4,000 /min. |
|                                   | Self drilling screw mode | 0 - 2,100 /min. |
|                                   | Soft mode                | 0 - 1,900 /min. |
| LED light                         | Yes                      |                 |
| Center height                     | 29 mm                    |                 |
| Dimensions (L x H)                | 114 x 241 mm             |                 |
| Weight <sup>1</sup> with BSL36A18 | 1.6 kg                   |                 |

<sup>1</sup> Weight according to EPTA-2004 procedure.

<sup>2</sup> Availability of versions may vary by country or area.

#### Characteristics

Compact and lightweight: only 114 mm short and 1.6 kg light allows working in narrow spaces with ease all day long

Powerful and fast: 210 Nm tightening torque for hardest jobs

Sensitive trigger starts fastening operation at 100 rpm so delicate screws don't get overtightened

Three bright LEDs for thorough illumination

IP56 rating due to coated electronics for full weather protection and against dust

5 modes for best adjustability and efficient work

Triple Hammer: hammer with 3 strikers reduces vibration by making 3 impacts per rotation instead of conventional 2 which results in greater comfort and less cam-out

Brushless motor for longest lifetime and highest efficiency

#### Further versions<sup>2</sup>

**WH18DCWRZ:** 2x battery BSL36A18, charger UC18YSL3.  
In stackable case HSC II

**WH18DCWFZ:** 2x battery BSL1850MA, charger UC18YFSL.  
In stackable case HSC II

**WH18DCWHZ:** 2x battery BSL1840M, charger UC18YFSL.  
In stackable case HSC II

**WH18DCW2Z:** Stackable case HSC II

**WH18DCW4Z:** Cardboard box

Read everything  
about our services at  
[hikoki-powertools.co.uk](http://hikoki-powertools.co.uk)

