

## UB18DB

Cordless Construction Light 18V 4966376402069



Dimmable 2,000 Lumen

Long runtime: up to 51 hours

IP54, and impact resistant design

1	нікокі	
7	0	F

Batteries not included

Specifications			
Voltage		18V	
Light source		LED	
Brightness	Min. power	350 Lumen	
	Max. power	2,000 Lumen	
Light color		5,000 K (daylight white)	
Colour rendering index		> 80 (natural colour appearance)	
Runtime with 5.0 Ah battery <sup>1</sup>	Min. power	32 hours	
	Max. power	6.5 hours	
Runtime with 8.0 Ah battery <sup>1</sup>	Min. power	51 hours	
	Max. power	10 hours	
USB power output		-	
Adjustable angle		360°	
IP certification		IP54	
Spark protected lens		-	
Impact resistant		Yes (IK08)	
Battery level display		Yes	
Dimensions (L x H x W)		202 x 140 x 162 mm	
Weight <sup>2</sup>		1.4 kg	

## Characteristics

High Lumen and stepless brightness adjustment for each situation Long runtime: fewer battery changes

Robust: ready for the toughest construction sites: proof against water, dust, and impact

Options for suspending, and fixing the construction light guarantee flexibility in all situations Mountable on tripods

Compatible with all HiKOKI 18V and MULTI VOLT batteries

Read everything about our services at **hikoki-powertools.com** 



<sup>1</sup> 5.0 Ah battery: BSL1850 or BSL36A18. 8.0 Ah battery: BSL36B18.

<sup>2</sup> Weight according to EPTA-Procedure 01/2014.

Non-contractual presentation photos, the machines are delivered without accessories unless otherwise stated. HiKOKI reserves the right to change certain technical characteristics, as well as the accessories supplied as standard. All products presented fall within the limit of the available stocks of HiKOKI Power Tools.

**HiKOKI 3 YEAR WARRANTY** More information about our conditions at **hikoki-powertools.com** 

