

NEW

C3606DUM

Cordless Circular Saw

36V - Ø165 mm - 66 mm

BRUSHLESS

Innovative Deep Cut Technology

Guide rail compatible

Fast stopping brake and kickback protection



Specifications

Voltage	36V
No-load speed	5,600 rpm
Saw blade diameter	165 mm
Mount hole diameter	20 mm
Max. cutting depth 90°	66 mm
Max. cutting depth 45°	43 mm
Max. cutting depth 90° on guide rail	61 mm
Bevel capacity	0° - 45°
Brushless motor	✓
Motor modes	3 (silent, medium, high)
Guide rail compatibility	✓
Deep Cut Technology	✓
Brake	✓
LED light	✓
Soft start	✓
Constant speed control	✓
Kickback protection	✓
Vacuum cleaner port	✓
Dimensions (L x W x H)	314 x 198 x 263 mm
Weight with BSL36A18X ¹	4.1 kg

Change the barcode placeholder 000000000000 into the specific one for the version that is shown

Characteristics

Equipped with innovative Deep Cut Technology for 61 mm cutting depth with guide rail and 66 mm without guide rail

Baseplate that is compatible with guide rails from HIKOKI, Festool, Makita, Bosch, Mafell, Milwaukee and Hilti

Optimal saw blade visibility from both sides for high-precision cuts

Fast stopping brake and kickback protection for high user safety

Very compact and lightweight for maximum flexibility

Highest power and robustness for high demanding and tough jobs

MULTI VOLT battery technology: AC power, DC freedom

Versions²

KSC3606DUMWP1Z: 2x battery BSL36A18X, fastcharger UC18YSL3, saw blade wood 165 mm, hex bar wrench, rip fence, stackable case HSC IV, 160 cm guide rail, cardboard box
000000000000

C3606DUMWPZ: 2x battery BSL36A18X, fastcharger UC18YSL3, saw blade wood 165 mm, hex bar wrench, rip fence, stackable case HSC IV
000000000000

KSC3606DUMW21Z: Saw blade wood 165 mm, hex bar wrench, rip fence, stackable case HSC IV, 160 cm guide rail, cardboard box
000000000000

C3606DUMW2Z: Saw blade wood 165 mm, hex bar wrench, rip fence, stackable case HSC IV
000000000000

¹Weight according to EPTA-2004 procedure.

²Standard accessories vary by country or area.

Read everything about our services at hikoki-powertools.eu



Change the URLs accordingly